

SP LED N

Svítidlo typu downlight



 [V] 220-240 AC	 [Hz] 50	 ≥15000	 [h] 15000	 ellipse ≤ 6x Nachdam	 Ra 80	 SMD
		 IP 20		 °C 5+25		
 [m] 0,09	 [mm²] 0,75	 0,5m	 CE	 EAC	 UKCA	



		 [W]		 [lm]	 [°]	 Tc [K]
SP LED N 6W WW-S	31074	6	bílá	370	110	3000
SP LED N 6W NW-S	31075	6	bílá	390	110	4000
SP LED N 12W NW-S	31079	12	bílá	900	110	4000
SP LED N 12W WW-R	31080	12	bílá	850	110	3000
SP LED N 12W NW-R	31081	12	bílá	900	110	4000
SP LED N 18W NW-S	31082	18	bílá	1350	110	4000
SP LED N 18W NW-R	31083	18	bílá	1350	110	4000

SP LED N je nová generace svítidel SP LED. Používají SMD LED diody. Svítidla jsou uzpůsobena pro montáž do podhledu s možností přeměny na přisazené svítidlo pomocí přidavného rámečku SP FRAME.

- Materiál korpusu: plast
- Materiál difuzoru: plast

SP LED N

Svítidlo typu downlight



SP LED N 6W NW-S




SP LED N 12W WW-R




SP LED N 18W NW-S




SP LED N 18W NW-R




SP LED N 6W-S



SP LED N 12W-R



SP LED N 18W-S



SP LED N 18W-R