



OTL 16



OTL 35



OTL 50

| | | | | |
|--------------|---|------------|------------|------------|
| Šedá | ● | MAA1016A10 | MAA1035A10 | MAA1050A10 |
| Modrá | ● | MAA1016B10 | MAA1035B10 | MAA1050B10 |
| Žluto-zelená | ● | MAA1016Y10 | MAA1035Y10 | MAA1050Y10 |
| Červená | ● | MAA1016R10 | - | MAA1050R10 |
| Černá | ● | MAA1016S10 | - | MAA1050S10 |

Technické údaje

| | | | |
|---|---|--|---|
| Rozsah upínaných vodičů Cu, Al (mm ²) | 1,5 - 16 | 2,5 - 35 | 1,5 - 50 |
| Jmenovité napětí AC / DC (V) | 1000 | 1000 | 1000 |
| Jmenovitý proud (A) | 82 (Cu) / 75 (Al) | 135 (Cu) / 120 (Al) | 160 (Cu) / 145 (Al) |
| Šířka / výška / délka (mm) | 13,5 / 39,5 / 45 | 16 / 40 / 45 | 18 / 43 / 50 |
| Šroub, inbus | č. 4 | č. 4 | č. 5 |
| Utahovací moment (Nm) | 1,5 Nm (1,5 - 6 mm ²) 7 Nm (10 - 16 mm ²) - | 3 Nm (2,5 - 16 mm ²) 6 Nm (25 - 35 mm ²) - | 1,5 Nm (1,5 - 2,5 mm ²) 5 Nm (4 - 10 mm ²) 10 Nm (16 - 50 mm ²) |
| Způsob uchycení | lišta DIN | lišta DIN | lišta DIN |
| Hmotnost (g) | 17 | 27 | 30 |
| Balení (ks) | 30 | 30 | ● 50 / ● ● ● ● 30 |

Rozměry

