Sensor-switched LED outdoor light

L 240 LED

Anthracite EAN 4007841 056506 Article number 056506







Outdoor light in a vertical design. Slimline, rectangular L 240 LED sensor-switched outdoor light in a vertical design. Elegant ambient lighting for entrances. Modern STEINEL LED technology with a light output of 570 lm at a power consumption of 7,5 W. Swivelling precision IR sensor with a 180° angle of coverage and 10 m reach.

Technical specifications

| Dimensions (L x W x H) | 81 x 165 x 305 mm |
|---|--------------------------|
| Mains power supply | 220 – 240 V / 50 – 60 Hz |
| Mounting height max. | 3,00 m |
| Sensor Technology | passive infrared |
| Output | 7,5 W |
| Interconnection | No |
| Slave modeselectable | No |
| Luminous flux | 570 lm |
| Efficiency | 76 lm/W |
| Colour temperature | 3000 K |
| Colour variation LED | SDCM3 |
| Farbwiedergabeindex | 80-89 |
| With lamp | Yes, STEINEL LED system |
| Lamp | LED cannot be replaced |
| LED life expectancy (max. °C) | 50000 h |
| Base | without |
| LED cooling system | Passive Thermo Control |
| With motion detector | Yes |
| Detection angle | 180 ° |
| Sneak-by guard | Yes |
| Capability of masking out individual segments | Yes |

| Electronic scalability | No |
|----------------------------|-------------------|
| Mechanical scalability | No |
| Reach, radial | r = 3 m (14 m²) |
| Reach, tangential | r = 10 m (157 m²) |
| Photo-cell controller | Yes |
| Twilight setting | 2 – 2000 lx |
| Time setting | 8 s – 35 Min. |
| Basic light level function | No |
| Soft light start | No |
| Impact resistance | IK07 |
| IP-rating | IP44 |
| Protection class | II |
| Ambient temperature | -20 – 50 °C |
| Housing material | Stainless steel |
| Cover material | Plastic, opal |
| Manufacturer's Warranty | 3 years |
| Settings via | Potentiometers |
| With remote control | No |
| Cover material | sticker |
| Version | Anthracite |
| PU1, EAN | 4007841056506 |
| | |


Sensor-switched LED outdoor light

L 240 LED

Anthracite EAN 4007841 056506 Article number 056506




Detection Zone



Mögliche Montagehöhe: 1,80 m – 3,00 m

Orange: radial Schwarz: tangential

Dimension Drawing



Circuit diagram

