

## ROUNDA V2LED

Svítlidlo typu "downlight"  
Svietidlo typu "downlight"



<b>[V]</b> 220-240 AC	<b>[Hz]</b> 50/60	<b>[°]</b> 110	<b>≥20000</b>	<b>[h]</b> 15000	<b>Ra ≥80</b>
<b>SMD</b>			<b>IP 44/20</b>		<b>5÷25</b>
	<b>[m]</b> 0,05	<b>[mm²]</b> 0,75	<b>0,5m</b>		<b>CE EAC</b>



	[W]		[°]	[lm]	[°]	[°K]
ROUNDA V2LED12W-NW-SN <b>27218</b>	12	nikl saténový / saténový nikel	780	110	4000	
ROUNDA V2LED18W-NW-SN <b>27219</b>	18	nikl saténový / saténový nikel	1250	110	4000	
ROUNDA V2LED24W-NW-SN <b>27220</b>	24	nikl saténový / saténový nikel	1700	110	4000	
ROUNDA V2LED6W-NW-SN <b>27221</b>	6	nikl saténový / saténový nikel	300	110	4000	
ROUNDA V2LED12W-NW-SR <b>28930</b>	12	stříbrná / strieborná	660	110	4000	
ROUNDA V2LED12W-NW-W <b>28931</b>	12	bílá / biela	780	110	4000	
ROUNDA V2LED12W-WW-W <b>28932</b>	12	bílá / biela	720	110	3000	
ROUNDA V2LED18W-NW-W <b>28934</b>	18	bílá / biela	1260	110	4000	
ROUNDA V2LED18W-WW-W <b>28935</b>	18	bílá / biela	1200	110	3000	
ROUNDA V2LED24W-NW-W <b>28936</b>	24	bílá / biela	1680	110	4000	
ROUNDA V2LED6W-NW-W <b>28937</b>	6	bílá / biela	330	110	4000	
ROUNDA V2LED6W-WW-W <b>28938</b>	6	bílá / biela	300	110	3000	



- Materiál krytu: hliníková slitina / Materiál pláště: hliníková zliatina
- Materiál stínidla: plast / Materiál tienidla: plast

## ROUNDA V2LED

Svítlidlo typu "downlight"  
Svietidlo typu "downlight"



ROUNDA V2LED12W-NW-SN



ROUNDA V2LED18W-NW-SN



ROUNDA V2LED24W-NW-SN



ROUNDA V2LED6W-NW-SN



ROUNDA V2LED12W-WW-W



ROUNDA V2LED18W-WW-W



ROUNDA V2LED24W-NW-W



ROUNDA V2LED6W-NW-W



## ROUNDA V2LED

Svítlidlo typu "downlight"  
Svietidlo typu "downlight"




ROUNDA V2LED6W-WW-W




ROUNDA V2LED12W-NW-W




ROUNDA V2LED12W-NW-SR




ROUNDA V2LED12W



ROUNDA V2LED18W



ROUNDA V2LED24W



ROUNDA V2LED6W

